



AIRE ACONDICIONADO PORTÁTIL P41



Control remoto

Kit de ventana incluido

Modo frío / calor

Temporizador 24h

MODELO

CÓDIGO EAN

HTW-PC-020P41

HTW-PC-026P41

HTW-PB-026P41

HTW-PC-035P41

HTW-PB-035P41

8435483866805

8435483866829

8435483866812

8435483866843

8435483866836

Alimentación eléctrica

V,F,HZ

220-240V (1 Fase ~ 50Hz)

RENDIMIENTO

Capacidad refrigeración	Capacidad	kW	2	2,6	2,6	3,5	3,5
	Consumo	W	785	1000	1000	1346	1346
	Corriente	A	3,5	4,5	4,5	5,9	5,9
	EER	W/W	2,6	2,6	2,6	2,6	2,6
	Clasificación Energética	Frío	A	A	A	A	A
Capacidad calefacción	Capacidad	kW			2,4		3,2
	Consumo	W			1043		1391
	Corriente	A			4,7		6,3
	COP	W/W			2,3		2,3
	Clasificación Energética	Calor			A		A

CARACTERÍSTICAS

Potencia sonora	dB(A)	65	65	65	65	65
Presión sonora	dB(A)	55	55	55	55	55
Caudal aire	m³/h	300	300	300	300	300
Perímetro climatizable (según las condiciones de la sala)	m²	10~16	12~18	12~18	14~20	14~20
Temperatura de operación	°C	18-35	18-35	18-35	18-35	18-35
Temperatura seleccionable	°C	16-31	16-31	16-31	16-31	16-31
Refrigerante	Tipo	R290	R290	R290	R290	R290
	Cantidad de carga	Kg	0,08	0,14	0,14	0,185

DIMENSIONES Y PESO

Dimensiones netas (AnxAlxPr)	mm	285x698x 335	285x698x 335	285x698x 335	285x698x 335	285x698x 335
Dimensiones brutas (AnxAlxPr)		340x885x 390	340x885x 390	340x885x 390	340x885x 390	340x885x 390
Peso neto	Kg	19	20	20	24	24

CONEXIONES

Longitud del tubo de evacuación	mm	1500	1500	1500	1500	1500
Diametro del tubo de evacuación	mm	150	150	150	165	165
Longitud del cable	mm	1800	1800	1800	1800	1800

*Según modelo