

Test Verification of Conformity

On the basis of the referenced test report(s), sample(s) of the below product have been found to comply with the harmonized standards and Directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product.

Once all product relevant **CE** mark directives are verified in compliance, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to product identical to the test sample(s) if the product complies with all relevant CE mark Directives requirements.

Applicant Name & Address	:	Ningbo Hongyi Electronics Technology Co., Ltd Guan Haiwei Industrial Zone East Area, Guan Haiwei Town, Cixi, Ningbo Zhejiang, 315314 P.R.China
Manufacturing site Name & Address		Company 1:Ningbo Hongyi Electronics Technology Co., Ltd Company 2:Cixi Hongyi Electronics Co.,Ltd. Common address:Guan Haiwei Industrial Zone East Area, Guan Haiwei Town, Cixi, Ningbo Zhejiang, 315314 P.R.China
Product(s) Tested	:	Cable reel for construction and installation sites
Ratings and principal characteristics	:	230V~, IP44, Class I, Non-rewirable, with 4 way DIN 49440-3 socket-outlets, with/without shutter, with a thermal cut out, with a non-rewirable plug with cord H07RN-F 3G1,5-2,5mm ² , detail product information see attachment.
Model(s)	:	HJR-56, HJR-57, HJR-62, HJR-56N, HJR-57N, HJR-62N
Brand name	:	HONGYI
Relevant Standard(s) / Specification(s) / Directive(s)	:	Low Voltage Directive 2014/35/EU
Verification Issuing Office Name & Address	:	Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Verification Number	:	160700051SHA-V1
Report Number(s)		160402743SHA-001+A1,160402743SHA-002+A1

NOTE 1: This verification is part of the full test report(s) and should be read in conjunction with it.

This Verification is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to copy or distribute this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this Verification are relevant only to the sample tested. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Oliver Wei Manager August 05, 2016



Annex to Test Verification of Conformity

This is an Annex to Test Verification of Conformity with 160700051SHA-V1. The issuing office is Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China

	Rated Power		
Туре	full-reeled /	Cord Information	Construction
	unreeled		
HJR-56	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	With shutter, with
	3000 W (13A)	Max. length 50m	metal panel.
HJR-57	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	With shutter, with
	3600 W (15,65A)	Max. length 50m	metal panel.
HJR-62	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	
	3000 W (13A)	Max. length 40m	With shutter, with
	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	plastic panel.
	3600 W (15,65A)	Max. length 50m	
HJR-56N	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	Without shutter, with
	3000 W (13A)	Max. length 50m	metal panel.
HJR-57N	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	Without shutter, with
	3600 W (15,65A)	Max. length 50m	metal panel.
HJR-62N	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	
	3000 W (13A)	Max. length 40m	Without shutter, with
	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	plastic panel.
	3600 W (15,65A)	Max. length 50m	

NOTE: This annex is part of the Test Verification of Conformity and should be read in conjunction with it.

This Verification is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to copy or distribute this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this Verification are relevant only to the sample tested. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

with

Oliver Wei Manager August 05, 2016



Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Caohejing Development Zone, Shanghai 200233, China Tel:86 21 6127 8200 Fax:86 21 6495 6263

Test Verification of Conformity

On the basis of the tests undertaken, the sample(s) of the below product have been found to comply with the requirements of the referenced specifications at the time the tests were carried out.

Applicant Name & Address	:	Ningbo Hongyi Electronics Technology Co., Ltd Guan Haiwei Industrial Zone East Area, Guan Haiwei Town, Cixi, Ningbo Zhejiang, 315314 P.R.China
Manufacturing site Name & Address		Company 1:Ningbo Hongyi Electronics Technology Co., Ltd Company 2:Cixi Hongyi Electronics Co.,Ltd. Common address:Guan Haiwei Industrial Zone East Area, Guan Haiwei Town, Cixi, Ningbo Zhejiang, 315314 P.R.China
Product(s) Tested	:	Cable reel for construction and installation sites
Ratings and principal characteristics	:	230V~, IP44, Class I, Non-rewirable, with 4 way DIN 49440-3 socket-outlets, with/without shutter, with a thermal cut out, with a non-rewirable plug with cord H07RN-F 3G1,5-2,5mm ² , detail product information see attachment.
Model(s)	:	HJR-56, HJR-57, HJR-62, HJR-56N, HJR-57N, HJR-62N
Brand name	:	HONGYI
Relevant Standard(s) / Specification(s) / Directive(s)	:	EN 61242:1997+A1:2008+ EK1 589-14 DIN VDE 0620-1:2016 DIN VDE 0620-2-1:2016+EK1 510-11:2011 GS-ET-35:2011 BGI/GUV-I 608:2012
Verification Issuing Office Name & Address	:	Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Verification Number	:	160700051SHA-V2
Report Number(s)		160402743SHA-001+A1,160402743SHA-002+A1

NOTE 1: This verification is part of the full test report(s) and should be read in conjunction with it.

This Verification is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to copy or distribute this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this Verification are relevant only to the sample tested. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Oliver Wei Manager August 05, 2016

GFT-OP-11b (24-Dec 2014)



Annex to Test Verification of Conformity

This is an Annex to Test Verification of Conformity with 160700051SHA-V2. The issuing office is Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China

	Rated Power		
Туре	full-reeled /	Cord Information	Construction
	unreeled		
HJR-56	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	With shutter, with
	3000 W (13A)	Max. length 50m	metal panel.
HJR-57	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	With shutter, with
	3600 W (15,65A)	Max. length 50m	metal panel.
HJR-62	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	
	3000 W (13A)	Max. length 40m	With shutter, with
	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	plastic panel.
	3600 W (15,65A)	Max. length 50m	
HJR-56N	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	Without shutter, with
	3000 W (13A)	Max. length 50m	metal panel.
HJR-57N	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	Without shutter, with
	3600 W (15,65A)	Max. length 50m	metal panel.
HJR-62N	1000 W (4,3A) /	H07RN-F 3G1,5 mm ² ,	
	3000 W (13A)	Max. length 40m	Without shutter, with
	1000 W (4,35A) /	H07RN-F 3G2,5 mm ² ,	plastic panel.
	3600 W (15,65A)	Max. length 50m	

NOTE: This annex is part of the Test Verification of Conformity and should be read in conjunction with it.

This Verification is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to copy or distribute this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this Verification are relevant only to the sample tested. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

tist

Oliver Wei Manager August 05, 2016